

IF IT WORX, IT'S



PRODUCT OVERVIEW



CONTENTS

COLOUR SYSTEMS

| | |
|----------------------------------|---|
| A3 Multifunctional Systems | 3 |
| A4 Multifunctional Systems | 5 |
| A4 Print Systems | 8 |

B/W SYSTEMS

| | |
|----------------------------------|----|
| A3 Multifunctional Systems | 9 |
| A4 Multifunctional Systems | 13 |
| A3 Print System | 17 |
| A4 Print Systems | 18 |

A3 MULTIFUNCTIONAL SYSTEMS



P-C2480i MFP

2507ci

3207ci

4007ci

COPY

| | |
|---------------------|---|
| Copy speed | 24 A4 pages/min, max 12 A3 pages/min in colour and in b/w |
| Copy resolution | 600 x 600 dpi |
| Greyscales | 256 |
| Standard paper feed | 600 (500 + 100 sheets) |
| Optional paper feed | 1 or 2 x 500 sheets |
| Paper capacity, max | 1,600 sheets |
| Paper format | A6R-A3 |
| Original feeder | Standard |
| Duplex | Standard |
| System memory | 1.5 GB (max 3 GB) |
| Zoom | 25%–400% |
| Cabinet | Option: no. 62 |

| | |
|---|---|
| 25 A4 / 12 A3 pages/min in colour and b/w | 32 A4 / 16 A3 pages/min in colour and b/w |
| 600 x 600 dpi | 600 x 600 dpi |
| 256 | 256 |
| 1,150 (2 x 500 + 150 sheets) | 1,150 (2 x 500 + 150 sheets) |
| 2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible | 2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible |
| 7,150 sheets | 7,150 sheets |
| A6R–SRA3/A3+ | A6R–SRA3/A3+ |
| Option: DP-7100, DP-7110, DP-7120 or DP-7130 | Option: DP-7100, DP-7110, DP-7120 or DP-7130 |
| Standard | Standard |
| 4 GB RAM, 32 GB SSD/ 320 GB HDD | 4 GB RAM, 32 GB SSD/ 320 GB HDD |
| 25%–400% | 25%–400% |
| Option: no. 76 | Option: no. 76 |

| |
|---|
| 40 A4 / 20 A3 pages/min in colour and b/w |
| 600 x 600 dpi |
| 256 |
| 1,150 (2 x 500 + 150 sheets) |
| 2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible |
| 7,150 sheets |
| A6R–SRA3/A3+ |
| Option: DP-7100, DP-7110 or DP-7130 |
| Standard |
| 4 GB RAM, 8 GB SSD/320 GB HDD |
| 25%–400% |
| Option: no. 76 |

PRINT

| | |
|-------------------|---|
| Type | Integrated within the system |
| Interfaces | USB 2.0, 10/100/1000BaseTX, USB host (2), NFC, Wi-Fi |
| Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.8 |
| Emulations | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIC, PDF 1.7 |

| | |
|---|---|
| Integrated within the system | Integrated within the system |
| USB 3.0, 10/100/1000BaseTX, USB host, NFC | USB 3.0, 10/100/1000BaseTX, USB host, NFC |
| Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9 |
| PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 1.7, XPS | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 1.7, XPS |

| |
|---|
| Integrated within the system |
| USB 3.0, 10/100/1000BaseTX, USB host, NFC |
| Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9 |
| PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 1.7, XPS |

NETWORK

| | |
|-------------------|--|
| Interfaces | 10/100/1000BaseTX |
| Network protocols | TCP/IP, Net BEUI |
| Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 |

| | |
|--|--|
| 10/100/1000BaseTX | 10/100/1000BaseTX |
| TCP/IP, Net BEUI | TCP/IP, Net BEUI |
| Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 |

| |
|--|
| 10/100/1000BaseTX |
| TCP/IP, Net BEUI |
| Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 |

SCAN

| | |
|-------------------|----------------------------|
| Scan type | CIS colour and b/w |
| Scan resolution | 200, 300, 400, 600 dpi |
| Interfaces | 10/100/1000BaseTX, USB 2.0 |
| Network protocols | TCP/IP |

| | |
|------------------------|------------------------|
| CCD colour and b/w | CCD colour and b/w |
| 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi |
| 10/100/1000BaseTX | 10/100/1000BaseTX |
| TCP/IP | TCP/IP |

| |
|------------------------|
| CCD colour and b/w |
| 200, 300, 400, 600 dpi |
| 10/100/1000BaseTX |
| TCP/IP |

FAX

| | |
|---------------------------|-------------------|
| Originals | max A3 |
| Modem speed | 33.6 kbps |
| Compression method | JBIG, MMR, MR, MH |
| One-touch dial/abbr. dial | 1,000/2,000 |

| | |
|-------------------|-------------------|
| max A3 | max A3 |
| 33.6 kbps | 33.6 kbps |
| JBIG, MMR, MR, MH | JBIG, MMR, MR, MH |
| 1,000/2,000 | 1,000/2,000 |

| |
|-------------------|
| max A3 |
| 33.6 kbps |
| JBIG, MMR, MR, MH |
| 1,000/2,000 |

Optional features are marked in orange font.

A3 MULTIFUNCTIONAL SYSTEMS



| | | 5007ci | 6007ci | 7307ci | 8307ci |
|---------------------------|---------------------|---|---|---|---|
| COPY | Copy speed | 50 A4 / 25 A3 pages/min in colour and b/w | 55 A4 / 27 A3 pages/min in colour, 60 A4 / 30 A3 pages/min in b/w | 65/73 A4 / 32/36 A3 pages/min in colour and b/w | 70/83 A4 / 35/41 A3 pages/min in colour and b/w |
| | Copy resolution | 600 x 600 dpi | 600 x 600 dpi | 600 x 600 dpi | 600 x 600 dpi |
| | Greyscales | 256 | 256 | 256 | 256 |
| | Standard paper feed | 1,150 (2 x 500 + 150 sheets) | 1,150 (2 x 500 + 150 sheets) | 4,150 (2 x 500 + 2 x 1,500 + 150 sheets) | 4,150 (2 x 500 + 2 x 1,500 + 150 sheets) |
| | Optional paper feed | 2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible | 2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible | 2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible | 2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible |
| | Paper capacity, max | 7,150 sheets | 7,150 sheets | 7,650 sheets | 7,650 sheets |
| | Paper format | A6R-SRA3/A3+ | A6R-SRA3/A3+ | A6R-A3+ | A6R-A3+ |
| | Original feeder | Option: DP-7100, DP-7110 or DP-7130 | Option: DP-7100, DP-7110 or DP-7130 | Standard | Standard |
| | Duplex | Standard | Standard | Standard | Standard |
| | System memory | 4 GB RAM, 8 GB SSD/320 GB HDD | 4 GB RAM, 8 GB SSD/320 GB HDD | 4.5 GB RAM, 8 GB SSD/320 GB HDD | 4.5 GB RAM, 8 GB SSD/320 GB HDD |
| | Zoom | 25%–400% | 25%–400% | 25%–400% | 25%–400% |
| | Cabinet | Option: no. 76 | Option: no. 76 | — | — |
| PRINT | Type | Integrated within the system | Integrated within the system | Integrated within the system | Integrated within the system |
| | Interfaces | USB 3.0, 10/100/1000BaseTX, USB host, NFC | USB 3.0, 10/100/1000BaseTX, USB host, NFC | USB 2.0, 10/100/1000BaseTX, USB host, NFC | USB 2.0, 10/100/1000BaseTX, USB host, NFC |
| | Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9 | Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ab OS 10.9 | Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ab OS 10.9 |
| | Emulations | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc |
| NETWORK | Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX | 10/100/1000BaseTX | 10/100/1000BaseTX |
| | Network protocols | TCP/IP, Net BEUI | TCP/IP, Net BEUI | TCP/IP, Net BEUI | TCP/IP, Net BEUI |
| | Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 |
| SCAN | Scan type | CCD colour and b/w | CCD colour and b/w | CCD colour and b/w | CCD colour and b/w |
| | Scan resolution | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi |
| | Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX | 10/100/1000BaseTX | 10/100/1000BaseTX |
| FAX | Network protocols | TCP/IP | TCP/IP | TCP/IP | TCP/IP |
| | Originals | max A3 | max A3 | max A3 | max A3 |
| | Modem speed | 33.6 kbps | 33.6 kbps | 33.6 kbps | 33.6 kbps |
| | Compression method | JBIG, MMR, MR, MH | JBIG, MMR, MR, MH | JBIG, MMR, MR, MH | JBIG, MMR, MR, MH |
| One-touch dial/abbr. dial | 1,000/2,000 | 1,000/2,000 | 1,000/2,000 | 1,000/2,000 | |

Optional features are marked in orange font.

A4 MULTIFUNCTIONAL SYSTEMS



| | 302ci | 350ci | 400ci | |
|----------------|---|---|---|---|
| COPY | Copy speed | 30 A4 pages/min in colour and b/w | 35 A4 pages/min in colour and b/w | 40 A4 pages/min in colour and b/w |
| | Copy resolution | 600 x 600 dpi | 600 x 600 dpi | 600 x 600 dpi |
| | Greyscales | 256 | 256 | 256 |
| | Standard paper feed | 600 (1 x 500 + 100 sheets) | 600 (1 x 500 + 100 sheets) | 600 (1 x 500 + 100 sheets) |
| | Optional paper feed | 1 x 500 + 2 x 500 or 1 x 2,000 sheets | 1 x 500 + 2 x 500 or 1 x 2,000 sheets | 1 x 500 + 2 x 500 or 1 x 2,000 sheets |
| | Paper capacity, max | 3,100 sheets | 3,100 sheets | 3,100 sheets |
| | Paper format | A6R-A4 | A6R-A4 | A6R-A4 |
| | Original feeder | Standard | Option: DP-5100 or DP-5110 | Option: DP-5100 or DP-5110 |
| | Duplex | Standard | Standard | Standard |
| | System memory | 1,536 MB RAM, (max. 3,072 MB RAM) | 2 GB RAM, 8 GB SSD/320 GB HDD | 2 GB RAM, 320 GB HDD |
| | Zoom | 25%-400% | 25%-400% | 25%-400% |
| | Cabinet | Option: high no. 74, low no. 75 | Option: high no. 74, low no. 75 | Option: high no. 74, low no. 75 |
| PRINT | Type | Integrated within the system | Integrated within the system | Integrated within the system |
| | Interfaces | USB 2.0 (opt.), 10/100/1000BaseTX, USB host (2) | USB 2.0 (opt.), 10/100/1000BaseTX, USB host (3) | USB 2.0 (opt.), 10/100/1000BaseTX, USB host (3) |
| | Operating systems | Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ab OS 10.9 | Windows XP, Vista, 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5 | Windows XP, Vista, 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5 |
| Emulations | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS | |
| NETWORK | Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX | 10/100/1000BaseTX |
| | Network protocols | TCP/IP, Net BEUI | TCP/IP, Net BEUI | TCP/IP, Net BEUI |
| | Operating systems | Windows 7/8/8.1/10, Server 2008/2008R2/2012/2012R2/2016/2019 | Windows XP, Vista, 7/8/8.1/10, Server 2003/2008 R2/2012 R2 | Windows XP, Vista, 7/8/8.1/10, Server 2003/2008 R2/2012 R2 |
| SCAN | Scan type | CCD colour and b/w | CCD colour and b/w | CCD colour and b/w |
| | Scan resolution | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi |
| | Interfaces | 10/100/1000BaseTX, USB 2.0 | 10/100/1000BaseTX, USB 2.0 | 10/100/1000BaseTX, USB 2.0 |
| | Network protocols | TCP/IP | TCP/IP | TCP/IP |
| FAX | Originals | max A4 | max A4 | max A4 |
| | Modem speed | 33.6 kbps | 33.6 kbps | 33.6 kbps |
| | Compression method | JBIG, MMR, MR, MH | JBIG, MMR, MR, MH | JBIG, MMR, MR, MH |
| | One-touch dial/abbr. dial | 1,000/2,000 | 1,000/2,000 | 1,000/2,000 |

Optional features are marked in orange font.

A4 MULTIFUNCTIONAL SYSTEMS



P-C2155w MFP

P-C2655w MFP

357ci

COPY

| | |
|---------------------|-----------------------------------|
| Copy speed | 21 A4 pages/min in colour and b/w |
| Copy resolution | 600 x 600 dpi |
| Greyscales | 256 |
| Standard paper feed | 300 (1 x 250 + 50 sheets) |
| Optional paper feed | 1 x 250 sheets |
| Paper capacity, max | 550 sheets |
| Paper format | A6R-A4 |
| Original feeder | Standard |
| Duplex | Standard |
| System memory | 512 MB (max 1,536 MB) |
| Zoom | 25%–400% |
| Cabinet | Option: no. 77 |

| | |
|---------------------|-----------------------------------|
| Copy speed | 26 A4 pages/min in colour and b/w |
| Copy resolution | 600 x 600 dpi |
| Greyscales | 256 |
| Standard paper feed | 300 (1 x 250 + 50 sheets) |
| Optional paper feed | 1 x 250 sheets |
| Paper capacity, max | 550 sheets |
| Paper format | A6R-A4 |
| Original feeder | Standard (Duplex-Scan) |
| Duplex | Standard |
| System memory | 512 MB (max 1,536 MB) |
| Zoom | 25%–400% |
| Cabinet | Option: no. 77 |

| | |
|---------------------|-----------------------------------|
| Copy speed | 35 A4 pages/min in colour and b/w |
| Copy resolution | 600 x 600 dpi |
| Greyscales | 256 |
| Standard paper feed | 350 (1 x 250 + 100 sheets) |
| Optional paper feed | 3 x 500 sheets |
| Paper capacity, max | 1,850 sheets |
| Paper format | A6R-A4 |
| Original feeder | Standard (Duplex-Scan) |
| Duplex | Standard |
| System memory | 1,024 MB RAM (max 3,072 MB RAM) |
| Zoom | 25%–400% |
| Cabinet | Option: high no. 72, low no. 73 |

PRINT

| | |
|-------------------|--|
| Type | Integrated within the system |
| Interfaces | USB 2.0, 10/100/1000BaseTX, USB-Host, SD-Slot, Wi-Fi |
| Operating systems | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6 |
| Emulations | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS |

| | |
|-------------------|---|
| Type | Integrated within the system |
| Interfaces | USB 2.0, 10/100/1000BaseTX, USB-Host, SD-Slot, Wi-Fi |
| Operating systems | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Linux, Mac ex OS 10.6 |
| Emulations | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS |

| | |
|-------------------|---|
| Type | Integrated within the system |
| Interfaces | USB 2.0, 10/100/1000 BaseTX, USB host (2) |
| Operating systems | Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ab OS 10.9 |
| Emulations | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS |

NETWORK

| | |
|-------------------|--|
| Interfaces | 10/100/1000BaseTX |
| Network protocols | TCP/IP, Net BEUI |
| Operating systems | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2 |

| | |
|-------------------|--|
| Interfaces | 10/100/1000BaseTX |
| Network protocols | TCP/IP, Net BEUI |
| Operating systems | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2 |

| | |
|-------------------|--|
| Interfaces | 10/100/1000BaseTX |
| Network protocols | TC P/IP, Net BEUI |
| Operating systems | Windows 7/8/8.1/10, Server 2008/2008R2/2012/2012R2/2016/2019 |

SCAN

| | |
|-------------------|----------------------------|
| Scan type | CIS colour and b/w |
| Scan resolution | 200, 300, 400, 600 dpi |
| Interfaces | 10/100/1000BaseTX, USB 2.0 |
| Network protocols | TCP/IP |

| | |
|-------------------|----------------------------|
| Scan type | CIS colour and b/w |
| Scan resolution | 200, 300, 400, 600 dpi |
| Interfaces | 10/100/1000BaseTX, USB 2.0 |
| Network protocols | TCP/IP |

| | |
|-------------------|----------------------------|
| Scan type | CCD colour and b/w |
| Scan resolution | 200, 300, 400, 600 dpi |
| Interfaces | 10/100/1000BaseTX, USB 2.0 |
| Network protocols | TCP/IP |

FAX

| | |
|---------------------------|-------------------|
| Originals | max A4 |
| Modem speed | 33.6 kbps |
| Compression method | JBIG, MMR, MR, MH |
| One-touch dial/abbr. dial | 22/100 |

| | |
|---------------------------|-------------------|
| Originals | max A4 |
| Modem speed | 33.6 kbps |
| Compression method | JBIG, MMR, MR, MH |
| One-touch dial/abbr. dial | 100/100 |

| | |
|---------------------------|-------------------|
| Originals | max A4 |
| Modem speed | 33.6 kbps |
| Compression method | JBIG, MMR, MR, MH |
| One-touch dial/abbr. dial | 100/200 |

Optional features are marked in orange font.

A4 MULTIFUNCTIONAL SYSTEMS



P-C3062i MFP

P-C3066i MFP

P-C3562i MFP

P-C3566i MFP

COPY

| | | |
|---------------------|-----------------------------------|-----------------------------------|
| Copy speed | 30 A4 pages/min in colour and b/w | 30 A4 pages/min in colour and b/w |
| Copy resolution | 600 x 600 dpi | 600 x 600 dpi |
| Greyscales | 256 | 256 |
| Standard paper feed | 350 (1 x 250 + 100 sheets) | 350 (1 x 250 + 100 sheets) |
| Optional paper feed | 3 x 500 sheets | 3 x 500 sheets |
| Paper capacity, max | 1,850 sheets | 1,850 sheets |
| Paper format | A6R-A4 | A6R-A4 |
| Original feeder | Standard | Standard |
| Duplex | Standard | Standard |
| System memory | 1,024 MB RAM (max 3,072 MB RAM) | 1,024 MB RAM (max 3,072 MB RAM) |
| Zoom | 25%–400% | 25%–400% |
| Cabinet | Option: high no. 72, low no. 73 | Option: high no. 72, low no. 73 |

| | |
|-----------------------------------|-----------------------------------|
| 35 A4 pages/min in colour and b/w | 35 A4 pages/min in colour and b/w |
| 600 x 600 dpi | 600 x 600 dpi |
| 256 | 256 |
| 350 (1 x 250 + 100 sheets) | 350 (1 x 250 + 100 sheets) |
| 3 x 500 sheets | 3 x 500 sheets |
| 1,850 sheets | 1,850 sheets |
| A6R-A4 | A6R-A4 |
| Standard (Duplex-Scan) | Standard (Duplex-Scan) |
| Standard | Standard |
| 1,024 MB RAM (max 3,072 MB RAM) | 1,024 MB RAM (max 3,072 MB RAM) |
| 25%–400% | 25%–400% |
| Option: high no. 72, low no. 73 | Option: high no. 72, low no. 73 |

PRINT

| | | |
|-------------------|---|---|
| Type | Integrated within the system | Integrated within the system |
| Interfaces | USB 2.0, 10/100/1000BaseTX, USB host (2) | USB 2.0, 10/100/1000 BaseTX, USB host (2) |
| Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5 |
| Emulations | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE Ilc, PDF 1.7, XPS | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE Ilc, PDF 1.7, XPS |

| | |
|---|---|
| Integrated within the system | Integrated within the system |
| USB 2.0, 10/100/1000BaseTX, USB host (2) | USB 2.0, 10/100/1000 BaseTX, USB host (2) |
| Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5 |
| PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE Ilc, PDF 1.7, XPS | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE Ilc, PDF 1.7, XPS |

NETWORK

| | | |
|-------------------|--|--|
| Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX |
| Network protocols | TCP/IP, Net BEUI | TC P/IP, Net BEUI |
| Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 |

| | |
|--|--|
| 10/100/1000BaseTX | 10/100/1000BaseTX |
| TCP/IP, Net BEUI | TC P/IP, Net BEUI |
| Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 |

SCAN

| | | |
|-------------------|----------------------------|----------------------------|
| Scan type | CCD colour and b/w | CCD colour and b/w |
| Scan resolution | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi |
| Interfaces | 10/100/1000BaseTX, USB 2.0 | 10/100/1000BaseTX, USB 2.0 |
| Network protocols | TCP/IP | TCP/IP |

| | |
|----------------------------|----------------------------|
| CCD colour and b/w | CCD colour and b/w |
| 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi |
| 10/100/1000BaseTX, USB 2.0 | 10/100/1000BaseTX, USB 2.0 |
| TCP/IP | TCP/IP |

FAX

| | | |
|---------------------------|----|-------------------|
| Originals | -- | max A4 |
| Modem speed | -- | 33.6 kbps |
| Compression method | -- | JBIG, MMR, MR, MH |
| One-touch dial/abbr. dial | -- | 100/200 |

| | |
|----|-------------------|
| -- | max A4 |
| -- | 33.6 kbps |
| -- | JBIG, MMR, MR, MH |
| -- | 100/200 |

Optional features are marked in orange font.

A4 PRINT SYSTEMS



P-C2650DW



P-C3062DN



P-C3562DN



P-C4072DN

| | | | | |
|-----------------------|--|--|--|--|
| Print format | A6R-A4 | A6R-A4 | A6R-A4 | A6R-A4 |
| Print speed | 26 A4 pages/min in colour and b/w | 30 A4 pages/min in colour and b/w | 35 A4 pages/min in colour and b/w | 40 A4 pages/min in colour and b/w |
| Print resolution | 600 x 600 dpi, 9,600 x 600 dpi level, 1,200 x 1,200 dpi (reduced speed) | 600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed) | 600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed) | 600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed) |
| Standard paper feed | 300 (1 x 250 + 50 sheets) | 600 (1 x 500 + 100 sheets) | 600 (1 x 500 + 100 sheets) | 600 (1 x 500 + 100 sheets) |
| Optional paper feed | 1 x 250 sheets | 3 x 500 sheets | 3 x 500 sheets | 3 x 500 sheets |
| Duplex | Standard | Standard | Standard | Standard |
| Processor | Cortex-A9 / 800 MHz | ARM Cortex-A9 dual core / 1.2 GHz | ARM Cortex-A9 dual core / 1.2 GHz | ARM Cortex-A9 dual core / 1.2 GHz |
| Print memory | 512 MB (max 512 MB) | 1,024 MB (max 1,024 MB) | 1,024 MB (max 3,072 MB) | 1,024 MB (max 3,072 MB) |
| Interfaces | USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi | USB 2.0, 10/100/1000BaseTX, USB host (2) | USB 2.0, 10/100/1000BaseTX, USB host (2) | USB 2.0, 10/100/1000BaseTX, USB host (2) |
| Network card optional | -- | IB-50 Gigabit Ethernet, IB-36 / IB-51 WLAN card | IB-50 Gigabit Ethernet, IB-36 / IB-51 WLAN card | IB-50 Gigabit Ethernet, IB-36 / IB-51 WLAN card |
| Emulations | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS |

A3 MULTIFUNCTIONAL SYSTEMS



1855

2256



P-2540i MFP

COPY

| | | |
|---------------------|---------------------------------|---------------------------------|
| Copy speed | 18 A4 / 8 A3 pages/min | 22 A4 / 10 A3 pages/min |
| Copy resolution | 600 x 600 dpi | 600 x 600 dpi |
| Greyscales | 256 | 256 |
| Standard paper feed | 400 (300 + 100 sheets) | 400 (300 + 100 sheets) |
| Optional paper feed | 3 x 300 sheets | 3 x 300 sheets |
| Paper capacity, max | 1,300 sheets | 1,300 sheets |
| Paper format | A6R-A3 | A6R-A3 |
| Original feeder | Option: DP-480 | Option: DP-480 |
| Duplex | Option: DU-480 | Option: DU-480 |
| System memory | 256 MB | 256 MB |
| Zoom | 25%–400% | 25%–400% |
| Cabinet | Option: high no. 68, low no. 69 | Option: high no. 68, low no. 69 |

| |
|----------------------------|
| 25 A4 / 12 A3 pages/min |
| 600 x 600 dpi |
| 256 |
| 600 (1 x 500 + 100 sheets) |
| 1 or 2 x 500 sheets |
| 1,600 sheets |
| A6R-A3 |
| Standard |
| Standard |
| 1 GB (max 3 GB) |
| 25%–400% |
| Option: no. 62 |

PRINT

| | | |
|-------------------|------------------------------------|------------------------------------|
| Type | Integrated within the system | Integrated within the system |
| Interfaces | USB 2.0 | USB 2.0 |
| Operating systems | Windows 7/8/8.1/10, Mac ex OS 10.5 | Windows 7/8/8.1/10, Mac ex OS 10.5 |
| Emulations | GDI | GDI |

| |
|---|
| Integrated within the system |
| USB 2.0, 10/100/1000BaseTX, USB host (2) |
| Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5 |
| PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe, PDF 1.7 |

NETWORK

| | | |
|-------------------|----|--------------------|
| Interfaces | -- | (optional) |
| Network protocols | -- | TCP/IP |
| Operating systems | -- | Windows 7/8/8.1/10 |

| |
|--|
| 10/100/1000BaseTX |
| TCP/IP, Net BEUI |
| Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019 |

SCAN

| | | |
|-------------------|--|--|
| Scan type | CIS colour and b/w | CIS colour and b/w |
| Scan resolution | 200, 300, 400 (only b/w), 600 (only b/w) dpi | 200, 300, 400 (only b/w), 600 (only b/w) dpi |
| Interfaces | USB 2.0 | USB 2.0 |
| Network protocols | -- | -- |

| |
|----------------------------|
| CIS colour and b/w |
| 200, 300, 400, 600 dpi |
| 10/100/1000BaseTX, USB 2.0 |
| TCP/IP |

FAX

| | | |
|---------------------------|----|-------------|
| Originals | -- | max A3 |
| Modem speed | -- | 33.6 kbps |
| Compression method | -- | MMR, MR, MH |
| One-touch dial/abbr. dial | -- | 32/120 |

| |
|-------------------|
| max A3 |
| 33.6 kbps |
| JBIG, MMR, MR, MH |
| 100/200 |

Optional features are marked in orange font.

A3 MULTIFUNCTIONAL SYSTEMS



| | 3262i | 4062i | |
|---------------------------|--|---|---|
| COPY | Copy speed | 32 A4 / 17 A3 pages/min | 40 A4 / 21 A3 pages/min |
| | Copy resolution | 600 x 600 dpi | 600 x 600 dpi |
| | Greyscales | 256 | 256 |
| | Standard paper feed | 1,100 (2 x 500 + 100 sheets) | 1,100 (2 x 500 + 100 sheets) |
| | Optional paper feed | 2 x 500 sheets or 2 x 1,500 | 2 x 500 sheets or 2 x 1,500 |
| | Paper capacity, max | 4,100 sheets | 4,100 sheets |
| | Paper format | A6R-A3 | A6R-A3 |
| | Original feeder | Option: DP-7100, DP-7110 or DP-7120 | Option: DP-7100, DP-7110 or DP-7120 |
| | Duplex | Standard | Standard |
| | System memory | 2 GB RAM, 32 GB SSD/ 320 GB HDD | 2 GB RAM, 8 GB SSD/ 320 GB HDD |
| | Zoom | 25%-400% | 25%-400% |
| | Cabinet | Option: no. 70 | Option: no. 70 |
| PRINT | Type | Integrated within the system | Integrated within the system |
| | Interfaces | USB 2.0, 10/100/1000BaseTX, USB host, NFC | USB 2.0, 10/100/1000BaseTX, USB host, NFC |
| | Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare , Linux, Mac ex OS 10.8 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare , Linux, Mac ex OS 10.8 |
| Emulations | PCL6 (5e, XL), KPDLL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe | PCL6 (5e, XL), KPDLL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe | |
| NETWORK | Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX |
| | Network protocols | TCP/IP, Net BEUI | TCP/IP, Net BEUI |
| | Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 |
| SCAN | Scan type | CCD colour and b/w | CCD colour and b/w |
| | Scan resolution | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi |
| | Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX |
| FAX | Network protocols | TCP/IP | TCP/IP |
| | Originals | max A3 | max A3 |
| | Modem speed | 33.6 kbps | 33.6 kbps |
| | Compression method | JBIG, MMR, MR, MH | JBIG, MMR, MR, MH |
| One-touch dial/abbr. dial | 1,000/2,000 | 1,000/2,000 | |

Optional features are marked in orange font.

A3 MULTIFUNCTIONAL SYSTEMS



| | | 5057i | 6057i |
|-------------------|--|---|---|
| COPY | Copy speed | 50 A4 / 25 A3 pages/min | 60 A4 / 30 A3 pages/min |
| | Copy resolution | 600 x 600 dpi | 600 x 600 dpi |
| | Greyscales | 256 | 256 |
| | Standard paper feed | 1,150 (2 x 500 + 150 sheets) | 1,150 (2 x 500 + 150 sheets) |
| | Optional paper feed | 2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible | 2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible |
| | Paper capacity, max | 7,150 sheets | 7,150 sheets |
| | Paper format | A6R-SRA3/A3+ | A6R-SRA3/A3+ |
| | Original feeder | Option: DP-7100, DP-7110 or DP-7130 | Option: DP-7100, DP-7110 or DP-7130 |
| | Duplex | Standard | Standard |
| | System memory | 4 GB RAM, 8 GB SSD/320 GB HDD | 4 GB RAM, 8 GB SSD/320 GB HDD |
| Zoom | 25%–400% | 25%–400% | |
| Cabinet | Option: no. 76 | Option: no. 76 | |
| PRINT | Type | Integrated within the system | Integrated within the system |
| | Interfaces | USB 3.0, 10/100/1000BaseTX, USB host, NFC | USB 3.0, 10/100/1000BaseTX, USB host, NFC |
| | Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9 |
| Emulations | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 1.7, XPS | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 1.7, XPS | |
| NETWORK | Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX |
| | Network protocols | TCP/IP, Net BEUI | TCP/IP, Net BEUI |
| | Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 |
| SCAN | Scan type | CCD colour and b/w | CCD colour and b/w |
| | Scan resolution | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi |
| | Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX |
| Network protocols | TCP/IP | TCP/IP | |
| FAX | Originals | max A3 | max A3 |
| | Modem speed | 33.6 kbps | 33.6 kbps |
| | Compression method | JBIG, MMR, MR, MH | JBIG, MMR, MR, MH |
| | One-touch dial/abbr. dial | 1,000/2,000 | 1,000/2,000 |

Optional features are marked in orange font.

A3 MULTIFUNCTIONAL SYSTEMS



| | 7057i | 8057i | |
|----------------|---|---|---|
| COPY | Copy speed | 70 A4 / 35 A3 pages/min | 80 A4 / 40 A3 pages/min |
| | Copy resolution | 600 x 600 dpi | 600 x 600 dpi |
| | Greyscales | 256 | 256 |
| | Standard paper feed | 4,150 (2 x 500 + 2 x 1,500 + 150 sheets) | 4,150 (2 x 500 + 2 x 1,500 + 150 sheets) |
| | Optional paper feed | 2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible | 2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible |
| | Paper capacity, max | 7,650 sheets | 7,650 sheets |
| | Paper format | A6R-A3+ | A6R-A3+ |
| | Original feeder | Standard | Standard |
| | Duplex | Standard | Standard |
| | System memory | 4.5 GB RAM, 8 GB SSD/320 GB HDD | 4.5 GB RAM, 8 GB SSD/320 GB HDD |
| | Zoom | 25%-400% | 25%-400% |
| Cabinet | -- | -- | |
| PRINT | Type | Integrated within the system | Integrated within the system |
| | Interfaces | USB 2.0, 10/100/1000BaseTX, USB host, NFC | USB 2.0, 10/100/1000BaseTX, USB host, NFC |
| | Operating systems | Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ab OS 10.9 | Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ab OS 10.9 |
| Emulations | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe | |
| NETWORK | Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX |
| | Network protocols | TCP/IP, Net BEUI | TCP/IP, Net BEUI |
| | Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 |
| SCAN | Scan type | CCD colour and b/w | CCD colour and b/w |
| | Scan resolution | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi |
| | Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX |
| | Network protocols | TCP/IP | TCP/IP |
| FAX | Originals | max A3 | max A3 |
| | Modem speed | 33.6 kbps | 33.6 kbps |
| | Compression method | JBIG, MMR, MR, MH | JBIG, MMR, MR, MH |
| | One-touch dial/abbr. dial | 1,000/2,000 | 1,000/2,000 |

Optional features are marked in orange font.

A4 MULTIFUNCTIONAL SYSTEMS



P-3521 MFP



P-3527w MFP



COPY

| | | |
|---------------------|-------------------------------|-------------------------------|
| Copy speed | 35 A4 pages/min | 35 A4 pages/min |
| Copy resolution | 600 x 600 dpi | 600 x 600 dpi |
| Greyscales | 256 | 256 |
| Standard paper feed | 350 (1 x 250 + 100 sheets) | 350 (1 x 250 + 100 sheets) |
| Optional paper feed | 2 x 250 sheets | 2 x 250 sheets |
| Paper capacity, max | 850 sheets | 850 sheets |
| Paper format | A6R-A4 | A6R-A4 |
| Original feeder | Standard | Standard |
| Duplex | Standard | Standard |
| System memory | 512 MB RAM (max 1.536 MB RAM) | 512 MB RAM (max 1.536 MB RAM) |
| Zoom | 25%–400% | 25%–400% |
| Cabinet | Option: no. 78 | Option: no. 78 |

PRINT

| | | |
|-------------------|---|---|
| Type | Integrated within the system | Integrated within the system |
| Interfaces | 10/100/1000BaseTX, USB 2.0, USB host, SD slot | 10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi |
| Operating systems | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Linux, Mac ex OS 10.6 | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Linux, Mac ex OS 10.6 |
| Emulations | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS |

NETWORK

| | | |
|-------------------|--|--|
| Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX |
| Network protocols | TCP/IP, Net BEUI | TCP/IP, Net BEUI |
| Operating systems | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2 | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2 |

SCAN

| | | |
|-------------------|----------------------------|----------------------------|
| Scan type | CCD colour and b/w | CCD colour and b/w |
| Scan resolution | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi |
| Interfaces | 10/100/1000BaseTX, USB 2.0 | 10/100/1000BaseTX, USB 2.0 |
| Network protocols | TCP/IP | TCP/IP |

FAX

| | | |
|---------------------------|----|-------------------|
| Originals | -- | max A4 |
| Modem speed | -- | 33.6 kbps |
| Compression method | -- | JBIG, MMR, MR, MH |
| One-touch dial/abbr. dial | -- | 100/200 |

A4 MULTIFUNCTIONAL SYSTEMS



P-4020 MFP

P-4025w MFP

P-4026iw MFP

COPY

| | | | |
|---------------------|-------------------------------|-------------------------------|-------------------------------|
| Copy speed | 40 A4 pages/min | 40 A4 pages/min | 40 A4 pages/min |
| Copy resolution | 600 x 600 dpi | 600 x 600 dpi | 600 x 600 dpi |
| Greyscales | 256 | 256 | 256 |
| Standard paper feed | 350 (1 x 250 + 100 sheets) | 350 (1 x 250 + 100 sheets) | 350 (1 x 250 + 100 sheets) |
| Optional paper feed | 2 x 250 sheets | 2 x 250 sheets | 2 x 250 sheets |
| Paper capacity, max | 850 sheets | 850 sheets | 850 sheets |
| Paper format | A6R-A4 | A6R-A4 | A6R-A4 |
| Original feeder | Standard (Duplex-Scan) | Standard (Duplex-Scan) | Standard (Duplex-Scan) |
| Duplex | Standard | Standard | Standard |
| System memory | 512 MB RAM (max 1.536 MB RAM) | 512 MB RAM (max 1.536 MB RAM) | 512 MB RAM (max 1.536 MB RAM) |
| Zoom | 25%–400% | 25%–400% | 25%–400% |
| Cabinet | Option: no. 78 | Option: no. 78 | Option: no. 78 |

PRINT

| | | | |
|-------------------|--|--|--|
| Type | Integrated within the system | Integrated within the system | Integrated within the system |
| Interfaces | 10/100/1000BaseTX, USB 2.0, USB host, SD slot | 10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi | 10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi |
| Operating systems | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Linux, Mac ex OS 10.6 | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Linux, Mac ex OS 10.6 | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Linux, Mac ex OS 10.6 |
| Emulations | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS |

NETWORK

| | | | |
|-------------------|--|--|--|
| Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX | 10/100/1000BaseTX |
| Network protocols | TCP/IP, Net BEUI | TCP/IP, Net BEUI | TCP/IP, Net BEUI |
| Operating systems | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2 | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2 | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2 |

SCAN

| | | | |
|-------------------|----------------------------|----------------------------|----------------------------|
| Scan type | CIS colour and b/w | CIS colour and b/w | CIS colour and b/w |
| Scan resolution | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi |
| Interfaces | 10/100/1000BaseTX, USB 2.0 | 10/100/1000BaseTX, USB 2.0 | 10/100/1000BaseTX, USB 2.0 |
| Network protocols | TCP/IP | TCP/IP | TCP/IP |

FAX

| | | | |
|---------------------------|----|-------------------|-------------------|
| Originals | -- | max A4 | max A4 |
| Modem speed | -- | 33.6 kbps | 33.6 kbps |
| Compression method | -- | JBIG, MMR, MR, MH | JBIG, MMR, MR, MH |
| One-touch dial/abbr. dial | -- | 100/200 | 100/200 |

A4 MULTIFUNCTIONAL SYSTEMS



P-4531 MFP

P-4536 MFP

P-4531i MFP

P-4536i MFP

COPY

| | | |
|---------------------|--|--|
| Copy speed | 45 A4 pages/min | 45 A4 pages/min |
| Copy resolution | 600 x 600 dpi | 600 x 600 dpi |
| Greyscales | 256 | 256 |
| Standard paper feed | 600 (1 x 500 + 100 sheets) | 600 (1 x 500 + 100 sheets) |
| Optional paper feed | 4 x 500 sheets | 4 x 500 sheets |
| Paper capacity, max | 2,600 sheets | 2,600 sheets |
| Paper format | A6R-A4 | A6R-A4 |
| Original feeder | Standard | Standard |
| Duplex | Standard | Standard |
| System memory | 1 GB RAM, (max 3 GB RAM), 32/128 GB SSD | 1 GB RAM, (max 3 GB RAM), 32/128 GB SSD |
| Zoom | 25%–400% | 25%–400% |
| Cabinet | Option: high no. 79, low no. 80 | Option: high no. 79, low no. 80 |

| | | |
|---------------------|--|--|
| Copy speed | 45 A4 pages/min | 45 A4 pages/min |
| Copy resolution | 600 x 600 dpi | 600 x 600 dpi |
| Greyscales | 256 | 256 |
| Standard paper feed | 600 (1 x 500 + 100 sheets) | 600 (1 x 500 + 100 sheets) |
| Optional paper feed | 4 x 500 sheets | 4 x 500 sheets |
| Paper capacity, max | 2,600 sheets | 2,600 sheets |
| Paper format | A6R-A4 | A6R-A4 |
| Original feeder | Standard | Standard |
| Duplex | Standard | Standard |
| System memory | 1 GB RAM, (max 3 GB RAM), 32/128 GB SSD | 1 GB RAM, (max 3 GB RAM), 32/128 GB SSD |
| Zoom | 25%–400% | 25%–400% |
| Cabinet | Option: high no. 79, low no. 80 | Option: high no. 79, low no. 80 |

PRINT

| | | |
|-------------------|---|---|
| Type | Integrated within the system | Integrated within the system |
| Interfaces | USB 2.0, 10/100/1000BaseTX, USB host | USB 2.0, 10/100/1000BaseTX, USB host |
| Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5 |
| Emulations | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS |

| | | |
|-------------------|---|---|
| Type | Integrated within the system | Integrated within the system |
| Interfaces | USB 2.0, 10/100/1000BaseTX, USB host | USB 2.0, 10/100/1000BaseTX, USB host |
| Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5 |
| Emulations | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS |

NETWORK

| | | |
|-------------------|--|--|
| Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX |
| Network protocols | TCP/IP, Net BEUI | TCP/IP, Net BEUI |
| Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 |

| | | |
|-------------------|--|--|
| Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX |
| Network protocols | TCP/IP, Net BEUI | TCP/IP, Net BEUI |
| Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 |

SCAN

| | | |
|-------------------|----------------------------|----------------------------|
| Scan type | CCD colour and b/w | CCD colour and b/w |
| Scan resolution | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi |
| Interfaces | 10/100/1000BaseTX, USB 2.0 | 10/100/1000BaseTX, USB 2.0 |
| Network protocols | TCP/IP | TCP/IP |

| | | |
|-------------------|----------------------------|----------------------------|
| Scan type | CCD colour and b/w | CCD colour and b/w |
| Scan resolution | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi |
| Interfaces | 10/100/1000BaseTX, USB 2.0 | 10/100/1000BaseTX, USB 2.0 |
| Network protocols | TCP/IP | TCP/IP |

FAX

| | | |
|---------------------------|----|-------------------|
| Originals | -- | max A4 |
| Modem speed | -- | 33.6 kbps |
| Compression method | -- | JBIG, MMR, MR, MH |
| One-touch dial/abbr. dial | -- | 22/100 |

| | | |
|---------------------------|----|-------------------|
| Originals | -- | max A4 |
| Modem speed | -- | 33.6 kbps |
| Compression method | -- | JBIG, MMR, MR, MH |
| One-touch dial/abbr. dial | -- | 100/200 |

Optional features are marked in orange font.

A4 MULTIFUNCTIONAL SYSTEMS



| | | P-5536i MFP | P-6036i MFP |
|----------------|---|---|---|
| COPY | Copy speed | 55 A4 pages/min | 60 A4 pages/min |
| | Copy resolution | 600 x 600 dpi | 600 x 600 dpi |
| | Greyscales | 256 | 256 |
| | Standard paper feed | 600 (1 x 500 + 100 sheets) | 600 (1 x 500 + 100 sheets) |
| | Optional paper feed | 4 x 500 sheets | 4 x 500 sheets |
| | Paper capacity, max | 2,600 sheets | 2,600 sheets |
| | Paper format | A6R-A4 | A6R-A4 |
| | Original feeder | Standard (Duplex-Scan) | Standard (Duplex-Scan) |
| | Duplex | Standard | Standard |
| | System memory | 1 GB RAM, (max 3 GB RAM), 32/128 GB SSD | 1 GB RAM, (max 3 GB RAM), 32/128 GB SSD |
| | Zoom | 25%–400% | 25%–400% |
| | Cabinet | Option: high no. 79, low no. 80 | Option: high no. 79, low no. 80 |
| PRINT | Type | Integrated within the system | Integrated within the system |
| | Interfaces | USB 2.0, 10/100/1000BaseTX, USB host | USB 2.0, 10/100/1000BaseTX, USB host |
| | Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5 |
| Emulations | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS | |
| NETWORK | Interfaces | 10/100/1000BaseTX | 10/100/1000BaseTX |
| | Network protocols | TCP/IP, Net BEUI | TCP/IP, Net BEUI |
| | Operating systems | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 | Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 |
| SCAN | Scan type | CCD colour and b/w | CCD colour and b/w |
| | Scan resolution | 200, 300, 400, 600 dpi | 200, 300, 400, 600 dpi |
| | Interfaces | 10/100/1000BaseTX, USB 2.0 | 10/100/1000BaseTX, USB 2.0 |
| | Network protocols | TCP/IP | TCP/IP |
| FAX | Originals | max A4 | max A4 |
| | Modem speed | 33.6 kbps | 33.6 kbps |
| | Compression method | JBIG, MMR, MR, MH | JBIG, MMR, MR, MH |
| | One-touch dial/abbr. dial | 100/200 | 100/200 |

Optional features are marked in orange font.

A3 PRINT SYSTEM



LP 3151

| | |
|---------------------|---|
| Print format | A6R-A3 |
| Print speed | 51 A4 / 26 A3 pages/min |
| Print resolution | 1,200 x 1,200 dpi |
| Standard paper feed | 1,200 (2 x 500 + 200 sheets) |
| Optional paper feed | 2 x 500, 3,000 sheets |
| Duplex | Standard |
| Processor | PowerPC 750FL/600 MHz |
| Print memory | 128 MB (max 640 MB) |
| Interfaces | IEEE 1284 parallel, USB 2.0, 10/100BaseTX, CF slot |
| Optional interfaces | -- |
| Emulations | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), Line Printer, Diablo 630, Epson LQ-B50, IBM Proprinter X24E, KCGL, PRESCRIBE IIe |

A4 PRINT SYSTEMS



P-3522DW

| | |
|---------------------|--|
| Print format | A6R-A4 |
| Print speed | 35 A4 pages/min |
| Print resolution | 600 x 600 dpi, 1,200 x 1,200 dpi |
| Standard paper feed | 350 (250 + 100 sheets) |
| Optional paper feed | 2 x 250 sheets |
| Duplex | Standard |
| Processor | Cortex-A9 / 800 MHz |
| Print memory | 256 MB (max 256 MB) |
| Interfaces | 10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi |
| Optional interfaces | -- |
| Emulations | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS |



P-4020DN

| | |
|---------------------|--|
| Print format | A6R-A4 |
| Print speed | 40 A4 pages/min |
| Print resolution | 600 x 600 dpi, 1,200 x 1,200 dpi |
| Standard paper feed | 350 (250 + 100 sheets) |
| Optional paper feed | 2 x 250 sheets |
| Duplex | Standard |
| Processor | Cortex-A9 / 800 MHz |
| Print memory | 256 MB (max 256 MB) |
| Interfaces | 10/100/1000BaseTX, USB 2.0, USB host, SD slot |
| Optional interfaces | -- |
| Emulations | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS |

P-4020DW

| | |
|---------------------|--|
| Print format | A6R-A4 |
| Print speed | 40 A4 pages/min |
| Print resolution | 600 x 600 dpi, 1,200 x 1,200 dpi |
| Standard paper feed | 350 (250 + 100 sheets) |
| Optional paper feed | 2 x 250 sheets |
| Duplex | Standard |
| Processor | Cortex-A9 / 800 MHz |
| Print memory | 256 MB (max 256 MB) |
| Interfaces | 10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi |
| Optional interfaces | -- |
| Emulations | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS |



P-4532DN

| | |
|---------------------|---|
| Print format | A6R-A4 |
| Print speed | 45 A4 pages/min |
| Print resolution | 1,200 x 1,200 dpi |
| Standard paper feed | 600 (500 + 100 sheets) |
| Optional paper feed | 4 x 500 sheets |
| Duplex | Standard |
| Processor | Cortex-A9 / 1.2 GHz |
| Print memory | 512 MB (max 2.5 GB) |
| Interfaces | 10/100/1000BaseTX, USB 2.0, USB host (2), SD slot |
| Optional interfaces | IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card |
| Emulations | PCL6 (5e, XL), KPDL 3 (PS 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS |



P-5032DN

| | |
|---------------------|---|
| Print format | A6R-A4 |
| Print speed | 50 A4 pages/min |
| Print resolution | 1,200 x 1,200 dpi |
| Standard paper feed | 600 (500 + 100 sheets) |
| Optional paper feed | 4 x 500 sheets |
| Duplex | Standard |
| Processor | Cortex-A9 / 1.2 GHz |
| Print memory | 512 MB (max 2.5 GB) |
| Interfaces | 10/100/1000BaseTX, USB 2.0, USB host (2), SD slot |
| Optional interfaces | IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card |
| Emulations | PCL6 (5e, XL), KPDL 3 (PS 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS |

P-5532DN

| | |
|---------------------|---|
| Print format | A6R-A4 |
| Print speed | 55 A4 pages/min |
| Print resolution | 1,200 x 1,200 dpi |
| Standard paper feed | 600 (500 + 100 sheets) |
| Optional paper feed | 4 x 500 sheets |
| Duplex | Standard |
| Processor | Cortex-A9 / 1.2 GHz |
| Print memory | 512 MB (max 2.5 GB) |
| Interfaces | 10/100/1000BaseTX, USB 2.0, USB host (2), SD slot |
| Optional interfaces | IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card |
| Emulations | PCL6 (5e, XL), KPDL 3 (PS 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS |

P-6033DN

| | |
|---------------------|---|
| Print format | A6R-A4 |
| Print speed | 60 A4 pages/min |
| Print resolution | 1,200 x 1,200 dpi |
| Standard paper feed | 600 (500 + 100 sheets) |
| Optional paper feed | 4 x 500 sheets |
| Duplex | Standard |
| Processor | Cortex-A9 / 1.2 GHz |
| Print memory | 512 MB (max 2.5 GB) |
| Interfaces | 10/100/1000BaseTX, USB 2.0, USB host (2), SD slot |
| Optional interfaces | IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card |
| Emulations | PCL6 (5e, XL), KPDL 3 (PS 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS |

PRODUCT OVERVIEW 01/2020

Your UTAX dealer

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.

UTAX Norderstedt
www.utax.com

UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names referred to are registered trademarks of the respective manufacturers.